

Practitioner's Docket No. 915-408

PATENT #4

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Jukka Wallenius et al

Serial No.: 10/010,924

Group No.: 2152

Filed: December 7, 2001

Examiner:

For: A METHOD FOR PROVIDING A USER INTERFACE TO A SUBSCRIBER
TERMINAL FOR CONFIGURING INTELLIGENT NETWORK SERVICES

Assistant Commissioner for Patents
Washington, D.C. 20231


TRANSMITTAL OF CERTIFIED COPY

Attached please find the certified copy of the foreign application from which priority is claimed for this case:

Country: EPO
Application Number: PCT/EP99/04052
Filing Date: June 11, 1999

WARNING: "When a document that is required by statute to be certified must be filed, a copy, including a photocopy or facsimile transmission of the certification is not acceptable." 37 C.F.R. 1.4(f) (emphasis added).

Reg. No.: 31,391



SIGNATURE OF PRACTITIONER

Francis J. Maguire

Tel. No.: (203) 261-1234

Ware, Fressola, Van Der Sluys & Adolphson LLP

(type or print name of practitioner)

Customer No. 004955

755 Main Street, P.O. Box 224

P.O. Address

Monroe, Connecticut 06468

NOTE: The claim to priority need be in no special form and may be made by the attorney or agent, if the foreign application is referred to in the oath or declaration, as required by § 1.63.


CERTIFICATE OF MAILING (37 CFR 1.8a)

I hereby certify that this correspondence is, on the date shown below, is being deposited with the United States Postal Service on the date shown below is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to the: Assistant Commissioner for Patents, Washington, D.C. 20231.

Date: March 8, 2002

Marilyn O'Connell

(Type or print name of person mailing paper)


(Signature of person mailing paper)

(Transmittal of Certified Copy [5-4])



Bescheinigung

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten internationalen Patentanmeldung überein.

Certificate

The attached documents are exact copies of the international patent application described on the following page, as originally filed.

Attestation

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet international spécifiée à la page suivante.

Den Haag, den
The Hague,
La Haye, le

04 12. 2001

Der Präsident des Europäischen Patentamts
Im Auftrag
For the President of the European Patent Office
Le Président de l'Office européen des brevets
p.o.

R.L.R. PETHER

Patentanmeldung Nr.
Patent application no. PCT/EP 99/04052
Demande de brevet n°



Anmeldung Nr.: PCT/EP 99/04052
Application no.:
Demande n°:

Anmelder: 1. NOKIA TELECOMMUNICATIONS OY - Espoo, Finland
Applicant(s): 2. WALLENIUS, Jukka - Nokia Group, Finland
Demandeur(s):

Bezeichnung der Erfindung:

Title of the invention: A METHOD FOR PROVIDING A USER INTERFACE TO A SUBSCRIBER
Titre de l'invention: TERMINAL FOR CONFIGURING INTELLIGENT NETWORK SERVICES

Anmeldetag:
Date of filing: 11 June 1999 (11.06.99)
Date de dépôt:

In Anspruch genommene Priorität(en)

Priority(ies) claimed
Priorité(s) revendiquée(s)

Staat:	Tag:	Aktenzeichen:
State:	Date:	File no.
Pays:	Date:	Numéro de dépôt:

Benennung von Vertragsstaaten : Siehe Formblatt PCT/RO/101 (beigefügt)
Designation of contracting states : See Form PCT/RO/101 (enclosed)
Désignation d'états contractants : Voir Formulaire PCT/RO/101 (ci-joint)

Bemerkungen:

Remarks:
Remarques:

PCT REQUEST

WO 23600

Original (for SUBMISSION) - printed on 11.06.1999 04:00:54 PM

IV-1	Agent or common representative; or address for correspondence The person identified below is hereby/has been appointed to act on behalf of the applicant(s) before the competent International Authorities as:	agent
IV-1-1	Name (LAST, First)	PELLMANN, Hans-Bernd
IV-1-2	Address:	Tiedtke-Bühling-Kinne et al. Bavariaring 4 D-80336 München Germany
IV-1-3	Telephone No.	+49 89 544690
IV-1-4	Facsimile No.	+49 89 532611
IV-1-5	e-mail	postoffice tbk-patent.com
IV-2	Additional agent(s)	additional agent(s) with same address as first named agent
IV-2-1	Name(s)	TIEDTKE, Harro; BÜHLING, Gerhard; KINNE, Reinhard; GRAMS, Klaus; LINK, Annette; VOLLNHALS, Aurel; LESON, Thomas, Johannes, Alois; TRÖSCH, Hans-Ludwig; CHIVAROV, Georgi; GRILL, Matthias; KÜHN, Alexander; OSER, Andreas; BÖCKELEN, Rainer
V	Designation of States	
V-1	Regional Patent (other kinds of protection or treatment, if any, are specified between parentheses after the designation(s) concerned)	AP: GH GM KE LS MW SD SZ UG ZW and any other State which is a Contracting State of the Harare Protocol and of the PCT EA: AM AZ BY KG KZ MD RU TJ TM and any other State which is a Contracting State of the Eurasian Patent Convention and of the PCT EP: AT BE CH&LI CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE and any other State which is a Contracting State of the European Patent Convention and of the PCT OA: BF BJ CF CG CI CM GA GN GW ML MR NE SN TD TG and any other State which is a member State of OAPI and a Contracting State of the PCT
V-2	National Patent (other kinds of protection or treatment, if any, are specified between parentheses after the designation(s) concerned)	AE AL AM AT AU AZ BA BB BG BR BY CA CH&LI CN CU CZ DE DK EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT UA UG US UZ VN YU ZA ZW

"A method for providing a user interface to a subscriber terminal for configuring intelligent network services"

Field Of the Invention

5

The present invention relates to a method for providing a user interface between a terminal device and a communication network for configuring intelligent network services. Particularly, the present invention relates to such an intelligent network (IN) supporting CAMEL (Customized Applications for Mobile network Enhanced Logic) and/or an MSP (Multiple Subscriber Profile) feature.

10

Background of the invention

15

Recently, the development of mobile telecommunication and the services offered thereby has made large progress. Particularly, mobile telecommunication systems now also permit access to so-called intelligent peripherals or offer an access to the Internet. Additionally, with an increasing number of services offered, there also arises a need for an individual configuration, for each respective user of a terminal device such as a mobile station, of the various services available. Such an individual and personal configuration of services in turn necessitates a corresponding interaction between the user himself and the network.

20

25

It is to be noted that, throughout the present specification, CAMEL and IN designates any solution in which a call, connection or session processing node contacts a service control function which issues instructions to the respective node. The contact to the service control function is based on a trigger information stored in the respective nodes. The trigger information may

30

35

specify situations in the course of a call, connection or session handling. The service control function may be internally distributed. Moreover, the corresponding IN protocol could be any protocol between a controlling
5 entity, such as a service controller (e.g. CAMEL Service Environment, CSE), responsive to a triggering from a call, and a session or connection processing node. The IN protocol may be e.g. an object oriented interface where the operations are object methods or invocations.

10

It is to be noted further that throughout the present specification, WAP and WTA designate any solution in which there is a content execution environment (user agent) at the terminal side and this environment is capable of
15 controlling terminal (MS) functionalities such as call control, mobility management MM and user interface. Furthermore, the execution environment may receive content from the network spontaneously or it may be provided with references to content to be downloaded. The content may be
20 hypertext, markup language code, any interpreted or even native or virtual machine code.

It is to be noted further, that throughout the present specification, MSP or subscriber profiles designate any
25 solution, in which in association with the service control function there are alternative predefined service provisionings, setting configurations and billed parties which can be selected by the user without separately changing the individual settings and provisionings. The
30 service control function implements these service profiles by differing service control depending on the profile selected and the service in the profile.

Currently, in intelligent networks (hereinafter also
35 referred to as IN-networks), a user interaction is provided

for by using in-band announcements and by relying on DTMF (Dual Tone Multiple Frequency) collection.

5 However, such procedures are often cumbersome and slow from a viewpoint of the user, especially in case the services are used frequently.

10 An alternative resides in the use of USSD (Unstructured Supplementary Services Data) based user interaction, but the problem with USSD is that USSD messages in itself without WAP content do not specify the formatting of the data to the user and the prompting. Similarly, with USSD more complex user dialogues are not possible. For instance, it is difficult for the user to enter multiple information
15 elements at a time in one USSD response, e.g. the user would have to enter delimiters after each information element.

20 Moreover, in a release for future GSM (Global System for Mobile communications) standards in the year 1998, there is defined a feature called multiple subscriber profile (MSP). This feature enables a respective subscriber to have several sets of provisioned services and several subscriber telephone numbers for his terminal, so-called MSISDN's. A
25 respective set of services is named a profile, and each profile is assigned at least one MSISDN. (A still further approach is to assign a respective MSISDN to each service feature of a profile).

30 The provisioning and the state of services is specific to a profile. For example, respective profiles can represent differently billed entities such as a company and a personal subscriber. Then, it could be possible for a user to select his company profile (defined by a profile
35 identification or profile ID) when he is doing business

calls, while he may select his private profile for effecting private calls.

5 The current working assumption in standardization on the implementation of the MSP feature is that it will be based on CAMEL.

10 However, up to now no proposal has been made regarding the implementation of a user interface for an MSP feature in a CAMEL network environment.

Independently therefrom, a WAP (Wireless Application Protocol) concept is currently being investigated in. According to the concept of WAP, a browser means or so-called user agent is specified for a terminal device (e.g. 15 mobile station MS). The browser means also supports a WTAI (Wireless telephony Applications Interface), which enables WAP WML scripts (Wireless Markup Language scripts) as a kind of executable instruction sets or executable program, 20 respectively, to interact with functions of the mobile station such as call control orientated functions. This means, that WML scripts receive event indications from a terminal and can request operations to be performed by the terminal. According to WAP, also applications are 25 supported, according to which a WAP server at the network side providing some content to the terminal side browsing means (user agent) can push WML pages (comparable to HTML pages) (HyperText Markup Language) to the terminal, i.e. to the terminal's user agent.

30

However, currently the WAP concept was not defined in terms of providing a user interface between a subscriber terminal and an intelligent network.

35 Summary of the invention

Consequently, the object of the present invention resides in the provision of a method for providing a user interface between a terminal device and a communication network for
5 configuring intelligent network services which is free from drawbacks as discussed above.

This object is achieved by a method for providing a user interface between a terminal device and a communication
10 network for configuring intelligent network services, said network comprising a service control entity (SCP, CSE) and a server entity communicating with each other via an interface, said service control entity being connected to at least one service switching device establishing
15 communication via at least one access network with said terminal device, and said terminal device being provided with a browsing means adapted to communicate with a user of said terminal device via a man machine interface means, and adapted to communicate with said server entity, the method
20 comprising the steps of: creating a content which constitutes a user interface for the control of a multiple subscriber profiles (MSP) feature; user interacting with the content; and modifying the state of the subscriber profiles in accordance with said user interaction.

25 Favorable refinements of the present invention are defined in the dependent claims.

More specifically, according to refinements of the present
30 invention:

- said state of subscriber profiles comprise the identity of the profile designated as the registered profile, and/or service states, and/or profiles selected for incoming or outgoing calls, and/or the execution states
35 of each service;

- the modifying the subscriber profiles state includes the selection of the profile to be used for an outgoing call;

- the modifying the subscriber profiles state includes
5 the selection of the profile to be used for an incoming call;

- said services states comprise service activity / inactivity and/or service parameters for each service;

- said content is loaded into said terminal device
10 (MS) in response to a predetermined event;

- said predetermined event is an IMSI attach, and/or a location updating, and/or a switching on of a new terminal for the user, and/or a subscriber profile registration request, and/or a supplementary service activation /
15 deactivation request, and/or a terminal device originated call set-up request, and/or a terminal device terminated call set-up request;

- said loading is effected from a subscriber identity module (SIM) to said terminal device mobile equipment part
20 (ME);

- said loading of said content is effected from a network element (WAP-SERVER) to said terminal device mobile equipment part (ME);

- said content is cached in said terminal device for
25 later events;

- said registered profile within the subscriber profiles state is maintained in the service control entity;

- the selection of said registered profile is communicated to the service control entity by said browsing
30 means;

- the selection of said registered profile is communicated to the service control entity by the content issuing a USSD or SMS message to said network, the network communicating the registered profile to the service control
35 entity;

- the selection of said registered profile is communicated to the service control entity by the content issuing a WSP / HTTP post method (wireless session protocol / hypertext transfer protocol) to said network, the network communicating the registered profile to the service control entity;

- said services states within the subscriber profiles state are maintained in the service control entity;

- said services states within the subscriber profiles state are maintained partly in the service control entity and partly in the GSM registers (HLR, VLR);

- a change in said services states is communicated to the service control entity by said browsing means;

- a change in said services state is communicated to the service control entity by the content issuing a USSD or SMS message to said network, the network communicating the registered profile to the service control entity;

- a change in said services state is communicated to the service control entity by the content issuing a WSP / HTTP post method (wireless session protocol / hypertext transfer protocol) to said network, the network communicating the registered profile to the service control entity,

- the selection of the subscriber profile to be used for a terminated call is performed by issuing a content push to said browser means; user interacting with the content; selected subscriber profile indicated to said server entity;

- the selection of the profile to be used for a terminated call is prompted from the user when the calling party dials a number not explicitly indicating the subscriber profile for the incoming call;

- the modifying of the state of the subscriber profiles includes the control of the execution of each service

- first the capabilities of the said terminal device (MS) and/or user agent capabilities are indicated to said server entity; the said content is selected on the said server entity based on the said capabilities; the said
5 selected content is downloaded to the said terminal device (MS);

- the capabilities of the said terminal device (MS) and/or user agent capabilities are indicated to said server entity If the mobile equipment part (ME) of the said
10 terminal device has changed since the latest power off of the said terminal device (MS);

- first said content is downloaded to said terminal device (MS), if it is discovered that such content is not already stored in said terminal device (MS);

15 - information on the downloaded services is inquired from said terminal device (MS) and the downloading of said content is performed only if it is not among said downloaded services;

- said content discovers the capabilities of said
20 network when the user attaches to the network or enters the area of a new service switching device (MSC, SSP);

- said content modifies the said user interface for the control of a multiple subscriber profiles feature in accordance with said capabilities of said network;

25 - said capabilities of the said network is the Camel feature version supported in said current service switching device (MSC, SSP);

- the capabilities of the said terminal device (MS) and/or browsing means are checked and compared to the
30 capability requirements of said content before said loading; and if the capability requirements are not satisfying, downloading said content from said network.

Also, the present invention concerns a correspondingly
35 adapted system for providing a user interface between a

terminal device (MS) and a communication network (IN-NW) for configuring intelligent network services, said system being adapted to operate according to the method presented above.

5

With the present invention being implemented, it advantageously provides an easier method of configuring services in an IN network. Moreover, this simplification can directly be seen by the user of the terminal, who, in
10 consequence, will be more willingly to configure the services he wants to use by his own. Additionally, this provides room for new services IN services which need to be configured by the user. For example, a configuration of a service may reside in turning on / off a service, inputting
15 other subscriber information such as a subscriber status (at work(cf. "business profile" mentioned above), at home (cf. "private profile" mentioned above, on vacation, etc.)). Likewise, by using the proposed interface, a subscriber may even be enabled to create services on his own.

20

Brief Description of the drawings

The present invention is now described herein below in detail by way of example with reference to the accompanying
25 drawings.

Fig. 1 shows a block diagram of a structure of an IN network;

30 Fig. 2 shows a signaling scenario in connection with an activation of MSP upon an IMSI attach as an event indication;

Fig. 3 shows a signaling scenario in connection with a
35 registration of a profile in connection with MSP;

Fig. 4 shows a signaling scenario for an outgoing call with a profile different from the registered profile;

- 5 Fig. 5 shows a signaling scenario for an outgoing call including a signaling for confirmation of the profile identity;

- Fig. 6 shows a signaling scenario for a standard
10 supplementary service activation for a profile implemented using CAMEL;

- Fig. 7 shows a flowchart which illustrates the overall procedure in setting of a profile of MSP at a flow chart
15 level without detailing an involved signaling;

- Fig. 8 (Figs. 8A & 8B) shows an additional signaling scenario according to the present invention for an MSP activation upon an IMSI attach;

20

Fig. 9 (Figs. 9A & 9B) shows a signaling scenario for a registration of supplementary services in a MSP environment according to a first way of implementation thereof;

- 25 Fig. 10 (Figs. 10A & 10B) shows a signaling scenario for a registration of supplementary services in a MSP environment according to a second way of implementation thereof;

- Fig. 11 shows a signaling scenario for the downloading of
30 MSP menus according to an embodiment; and

Fig. 12 shows a signaling scenario for a subscriber profile selection in case of an incoming call using WTA;
particularly such a signaling scenario in connection with a

mobile originated call in case a service user interface has not been downloaded to the terminal;

Detailed Description of preferred embodiments

5

Hereinafter, the present invention is now described in detail with reference to the drawings.

For still better understanding, the architecture of an intelligent network (IN network) is briefly described at first with reference to Fig. 1.

As shown in Fig. 1, an intelligent network as a communication network for intelligent network services comprises different IN network entities. For easier understanding, the following explanations omit the add-on of "entity" but rather refer to the network entities by their functional description. Also, as is current practice in standardization documents, the entities are referred to by using the abbreviation thereof after having been defined once.

Now, among these, a service creation environment SCE communicates with a service management system SMS. The SMS in turn communicates with a service control point SCP. In a CAMEL network environment, the service control point is also referred as CAMEL service environments CSE. Associated to the CSE, a WAP server is provided for, which is connected to the SCE via a WAP based interface WAP-I/F. Although in Fig. 1 the WAP server and the CSE are illustrated as being separated from each other, they can be implemented in a single network node only, without necessitating any change to the present invention.

The SCP (or CSE in case of CAMEL) communicates via an interface SS#7-I/F adapted to the signaling system No. 7 with components of a PLMN network (Public Land Mobile Radio Network). Namely, the SCP communicates with a service
5 switching point SSP. Such a SSP may be represented in a PLMN by a mobile switching center MSC, to which a home location register HLR and/or visitor location register VLR can be associated.

10 The MSC as a SSP communicates with a base station subsystem BSS consisting of at least one base station controller BSC controlling at least one base transceiver station BTS.

A respective BTS communicates via an air interface AIR-I/F
15 with a terminal device such as a mobile station MS operated by a user.

More specifically, such a terminal MS, among other means (not shown) is, in connection with the present invention,
20 provided with a WAP user agent or WAP browsing means, respectively. Generally, a user agent is any device adapted to interpret resources. The WAP user agent is adapted to communicate with the user via a man machine interface means MMI. Additionally, the WAP user agent is adapted to access
25 a repository associated thereto. The repository is a persistent storage container as a kind of memory means storing WTA event catalogues and other pre-loaded WTA contents in connection with data used in connection with WAP.

30 Finally, the WAP user agent communicates (indicated by the dotted line in Fig. 1) by an intermediate WAP gateway WAP-GW with the WAP server associated to the CSE.

The communication path illustrated by the dotted line "passes through" the PLMN network, while however the information transmitted thereon are transparent for the PLMN network and can be regarded as being exchanged between
5 the WAP gateway and the WAP user agent directly.

A corresponding signaling between the above introduced devices in order to implement and/or carry out the present invention will subsequently be described for different
10 situations occurring in the network, with reference to Figs. 2 to 12.

In these Figures, those components as briefly explained in connection with Fig. 1 are schematically shown with the
15 corresponding signaling over time, i.e. signals communicated there between, being indicated as arrows.

When applied to the MSP feature of a CAMEL based network, according to the present invention, the implementation of
20 an MSP user interface shall be based on the above briefly explained WAP concept and the use of the WTAI (Wireless Telephony Applications Interface). MSP menus and corresponding WML scripts are stored in a SIM (Subscriber Identity Module) card by the operator of the network, or
25 they may be downloaded to the terminal in accordance with a method as explained in connection with Fig. 2. A corresponding WML script checks the support of CAMEL MSP features upon the detection of (predetermined) event indications such as for example location updates, etc.. If
30 MSP is supported by the network, corresponding MSP menus are activated in the WAP user agent. Furthermore, if subscriber profiles, i.e. MSP profiles, are to be managed, the MSP menus use WML URL methods to request/contact the WAP server, and the WAP server in turn interacts with the
35 CSE network entity. The WAP pages and their WML scripts

using WTAI enable the user interfaces to be defined for several MSP functions such as profile registration, explicit profile selection during call attempts and alternative profile service management etc.

5

Thus, the terminal checks (e.g. in connection with an occurrence of an event indication such as a network attach, a location update to a new location area, a subscriber profile registration request, or a supplementary service activation request) whether the network supports the CAMEL MSP feature. If this is the case, the MSP menus are activated in the WAP user agent (or downloaded thereto). The subsequent interactions towards the CAMEL CSE are effected using WAP substantially as described above.

15

Although herein above and subsequently, it is generally referred to WML scripts and URL and other associated terminology without going into detail, it is deemed that those skilled in the art perfectly understand the detailed technical meaning thereof. Hence, a full and detailed explanation thereof is considered to be dispensable, since the present invention will also become apparent to the reader without setting out every detail of WAP and WTAI.

20

Furthermore, it should be noted that currently supplementary services can be either standardized GSM supplementary services, which are based on service execution in the switches, or as IN based services. It must be noted that the following is applicable for any supplementary services which can be implemented either by service execution in the switches or as IN based. What is said about Camel versions is also applicable for the versions of any IN architecture such as American Wireless Intelligent Network (WIN).

30

35

If it is desired to have more than one subscriber profile, then some of the services have to be implemented as IN based, this is due to the fact that only one set of supplementary services and their associated data is supported by GSM registers and the GSM MAP signaling. However, currently only a subset of GSM supplementary services can be re-implemented as IN based. This leads essentially to two solutions in the implementation of multiple subscriber profiles. First solution is that one of the profiles contains standardized GSM supplementary services and the other profiles contain IN based variants of the same services. The second solution is that all the supplementary services that can be included in more than one profile are implemented as IN based, all the rest of the supplementary services shall be active according to their settings over all the profiles.

In either case, the when a user controls a supplementary service or manages the service data associated with the supplementary service, it must be known whether the service is IN based or standard GSM supplementary service based. If it is desired to hide from the user the fact whether in the current registered profile, in which a given service is managed or controlled, the service is IN based or GSM supplementary service based, the WML content must know how the service is implemented and provide an interface that hides this fact. This means that when receiving user input, the WML content deduces depending on the information on the current registered profile, which service management or control procedures must be applied. The management and control procedures can be the sending of unstructured messages (USSD, SMS or WSP post method) in the case of IN based services and standardized GSM SS service control and management procedures in the case of GSM SS based services.

When different versions of Camel are supported in different networks, the set of services that can be included in the alternative subscriber profiles are different, because the set of IN based services is different. In a given Camel
5 version a service can be implemented as IN based, but in the earlier versions it cannot. This means that the WML content must be aware of the Camel version so that it can be known which of the services can be in more than one profile and which are independent of the profiles or
10 alternatively which of the IN based services in the alternative profiles are available. This effect of the Camel version on the available services and on the providing of services in more than one subscriber profile shall be called hereafter the MSP version. This means that
15 when receiving user input, the WML content must also check the MSP version to deduce which service management or control procedures must be applied.

Depending on the Camel version, different user interfaces
20 can be presented by the WML content to the user. In an embodiment of the invention, the services that are supported as IN based are shown in association with more than one subscriber profile. Preferably, there can be sub-menus for each of the different profiles and a sub-menu
25 for the rest of the services not included in the different profiles. The services not included in the different profiles shall be active or inactive according to their own settings over all the different profiles. In this way they are independent of the different profiles. Depending on the
30 Camel version the amount of the services in the sub-menus for the different profiles may vary. Similarly, depending on the Camel version the amount of the services in the sub-menu for the services not included in the profiles may vary. When a service is not available as IN based to be
35 included in the different profiles, it can be moved to the

sub-menu for the services independent of the profiles.
Alternatively, the services not available as IN based are
just marked as not applicable in the sub-menus for the
different profiles. The user may be instructed to use the
5 generic service, which is in effect over all the profiles.

In the following, a description is given of cases, in which
the WAP /WTAI principle method and/or functionality is used
in connection with the CAMEL MSP feature as an example. It
10 should be noted that the details of the interaction between
the WAP server and user agent are, for the above reason,
not explained in every detail in connection with the
following description of Figs. 2 to 7.

15 Fig. 2 shows a signaling scenario in connection with an
activation of MSP upon an IMSI attach as an event
indication.

In this case, two options are conceivable and therefor to
20 be distinguished from each other.

According to option A, in a step S51, an indication of an
IMSI (International Mobile Subscriber Identity) attach is
forwarded from a home location register HLR as a part of
25 the service switching point SSP of the network to the CSE.
This indication includes, for example, the CAMEL phase and
the attaching terminal's WAP capability (WAP capability
being often also referred to as terminal MS capability). At
the CSE, in step S52, it is checked whether the network
30 provisions and/or supports MSP. (Also, the CSE may check
from a MExE server(not shown in Fig. 1) as an entity
caching MS terminal capability information, the terminal
capability information cached.)

According to option B, however, a subscriber identity module SIM or the terminal MS itself contains an application (e.g. WML script) which is responsive to an IMSI attach as an event indication, and which checks the terminal's MC capabilities and reports them to the CSE, as indicated in step S53. (Also, in connection with the MExE server alternative mentioned above, the step S53 may be replaced by an indication to the CSE from the MExE server as soon as MS terminal capabilities are obtained from the MS to the MExE server.) In a subsequent step S54, the CSE checks for the MSP service being downloaded, and if this is not the case, downloading of the MSP service to the terminal station, namely to its user agent is initiated. Then, in a step S55, the serving network is checked in regards of the CAMEL phase or CAMEL version it supports, and in step S56 the corresponding MSP version is reported from the CSE to the user agent.

Then, the MSP menu is modified depending on the degree of services available (determined by the MSP version), while services currently not available (in the current MSP version) are omitted from the MSP menus. Alternatively, the services not supported in the current environment are indicated as not applicable in the current environment, e.g. by dimming the text color or modifying the font otherwise for the selections associated with the services. In an embodiment of the invention, the user observes different services under profile based management and control depending on the MSP version supported. This means that in one MSP version a given service can be included in the different alternative profiles while in another MSP version the service can only be generic which means that its status, settings and control are independent of the profile selected. The following user-network interaction

(not shown in this figure) is essentially in line with the WAP /WTAI principles mentioned earlier before.

It is to be noted that the entity capable of downloading
5 MSP menus to the terminal MS is provided with the
indication of MS terminal capabilities after activation of
a new terminal, e.g. during location updating. Also, step
S55 could be before step S54, if the whole MSP menus code
is different per MSP version (which is enabled by present
10 CAMEL phase). The description has been made under the
assumption that within the downloaded menu code there is
parameterisation, which may alter the menus downloaded
depending on the MSP version. For example, some menu
selections could be dimmed and thus be not available for
15 selection, if the service to be specified thereby is not
available.

Fig. 3 shows a signaling scenario in connection with a
registration of a profile in connection with MSP. In a step
20 S61, a user forwards a command for selection of MSP menus
to the user agent. At the user agent, in step S62, an MSP
content is retrieved from a terminal repository. Then, the
user forwards (via the MMI shown in Fig. 1) a profile
registration request to the user agent. The user agent
25 acknowledges this request by transmitting, step S64, a
"select profile" indication to the user, indicating that a
selection of a profile is now possible. In step S65, the
user selects a profile and the selected profile is informed
to the user agent in form of a transmitted profile identity
30 of profile ID. The user agent then transmits the profile ID
in step S66 as a USSD/SMS message (Unstructured
Supplementary Data/SMS) to the CSE, and the CSE as the SCP,
in step S67, returns a message indicating that the profile
is registered to the user agent.

Fig. 4 shows a signaling scenario for an outgoing call with a profile different from the registered profile.

For the subsequent explanations, it is assumed that the MSP feature is defined as comprising two different profiles, which are distinguishable by the respective MSISDN number, namely a first profile (e.g. Profile ID = 1) being assigned an MSISDN-A comprising business call service features, for example, and a second profile (e.g. Profile ID = 2) being assigned an MSISDN-B comprising private call service features, for example. Further, the profile 2 (MSISDN-B) is assumed to be the registered one.

Then, the flow proceeds as follows. In a step S71, the user selects menus for an outgoing call at the user agent. At the user agent side, in a step S72, the MSP content is retrieved from the terminal's repository, and in step S73, an invitation to the user to select a type of an outgoing call such as business call (type/ID 1) or private call (type/ID 2) is forwarded from the user agent. The user in turn selects a desired type (here, according to the illustrated example, he selects type 1 (MSISDN-A)) and the information of the selected type is forwarded in step S74 to the user agent. It must be noted that a currently selected user profile can also be stored to the ME/SIM. This means that it is possible for the MS/User Agent to explicitly indicate the profile used in each outgoing call set-up information e.g. in a called party number-prefix. This provides the advantage that the current profile does not necessarily need to be registered to the network.

Subsequently, the user agent, in step S76, initiates a call setup by an MSP content such as for example by using a WTAI setup message including the MSISDN-B as the MSISDN of the (according to the above assumption) registered profile

together with a profile ID prefix of the selected profile. This setup message is transmitted to the MSC as a service switching point. In step S76, the MSC transmits an InitialDp message including the MSISDN-B together with the profile ID prefix of the selected profile type to the CAMEL service environment CSE. In step S77, the CSE returns a FurnishChargingInformation message to the MSC based on the profile ID of the prefix, and in a subsequent step S78 issues a connect command to the MSC based on the changed MSISDN, i.e. on MSISDN-A. Thus, the selected profile has, for this case of a specific call, replaced the registered profile.

Fig. 5 shows a signaling scenario for an outgoing call including a signaling for confirmation of the profile identity. The same assumptions as made above in connection with Fig. 4 hold for this case.

In step S81, the user starts an outgoing call by forwarding a corresponding instructions to the user agent. The user agent in step S82 forwards a setup message/instruction based on the registered profile (MSISDN-B) without a profile ID prefix to the MSC. Again, the MSC forwards, in step S83, an InitialDp message, including said MSISDN-B but without a profile ID prefix, to the service control point CSP (CSE). In response thereto, in step S84 the CSE returns a ConnectToResource CTR command and PlayAnnouncementCollectUserInformation PACUI command to the MSC. In order to collect user information, the MSC transmits to the user an invitation to confirm the profile (step S85). The user responds in step S86 by a profile confirmation message transmitted to the MSC, and the SCP-CSE returns a FurnishChargingInformation message to the MSC based on the (thus confirmed) profile ID (step S87). Thereafter, the CSE issues a connect command to the MSC

based on the unchanged MSISDN, i.e. on MSISDN-B,
representing the (registered) confirmed profile.

Fig. 6 shows a signaling scenario for a standard
5 supplementary service activation for a profile implemented
using CAMEL. In a step S91, a user activates a standard
supplementary service such as for example a call hold
service. This activation signal is transmitted to the user
agent, at which in a step S91a, the WML content of a
10 corresponding WML script intercepts a standard user
interface signal, and in step S91b, a call hold functional
command is intercepted. Then, in step S92, a corresponding
USSD or DTMF signal is forwarded to the service control
point, which returns in step S93 call party handling
15 commands to the MSC as a service switching point, so that
the call is held.

The WML content can be deduced based on the currently
supported version of MSP feature, i.e. whether the
20 supplementary service is available as a standardized
version or as a CAMEL based service. Depending on this
deduction, it can issue either the GSM supplementary
service activation command to the MSC or the USSD/DTMF
based activation command intercepted to the CSE.

25

Fig. 7 shows a flowchart which illustrates the overall
procedure in setting of a profile of MSP at a flow chart
level without detailing an involved signaling.

30 The process starts in step S100. In a subsequent step S101
it is checked for the occurrence of an event indication
such as, for example, an IMSI attach or location area
update. If no such event indication is present (NO in step
S101), the flow returns and loops until an event indication
35 is present (YES in step S101).

If the loop is ended, the flow proceeds to step S102, in which the network to which e.g. the terminal attaches, supports the MSP functional feature. If the network does
5 not support MSP, the flow proceeds to step S103, according to which a default profile is to be used for the further process and/or call and the flow ends in step S107.

If, however, it is determined in step S102 that the network
10 NW supports MSP (YES in step S102), the flow branches to step S104 and the MSP menus are activated at the WAP user agent. Thereafter, the user may select one of available MSP profiles in step S105. (If no selection is performed, this has to be regarded as the selection of the default
15 profile). In step S106, the previously selected profile is then activated and the terminal and network communicate with each other using the selected profile. The flow then ends in step S107.

20 Fig. 8 illustrates an additional method for MSP activation upon detection of an IMSI attach as a predetermined event.

In a step S81, the HLR forwards an indication of an IMSI attach to the CSE as a SCP. In case of a successful attach
25 procedure, the terminal MS forwards, step S82, a corresponding event report to the user agent associated thereto. Subsequently, the user agent capabilities and downloaded software components are forwarded and informed to the WAP server, step S83. The information on downloaded
30 software components may also be indicated to the CSE via the WAP server separately. The WAP server in step S84 relays this information to the CSE as the service control point, which, in a follow up step S85, checks if MSP is provisioned or not. In a subsequent step S86, the serving
35 network is checked in terms of which CAMEL phase it

supports and the user agent capabilities are checked. (Note that steps S85 and S86 are performed at the CSE side.) As a result, the MSP version is determined.

- 5 At this stage of the method, the flow branches and two cases have to be distinguished as shown in Fig. 8B.

According to a case A, the MSP service is assumed to be not already downloaded to the terminal's user agent. Then, in a
10 step S87a, if the MSP service is not downloaded, or if the terminal type was modified since the latest IMSI attach, the downloading of the MSP menus is started. In consequence, in a step S88a, a WTA catalogue and the MSP menu contents are downloaded from the CSE to the MS and/or
15 its user agent.

According to a case B, the MSP service is assumed to be downloaded. Then, in a step S87b, if said MSP service is already downloaded, the MSP version is indicated and the
20 corresponding version information is forwarded from the CSE to the terminal and/or user agent, respectively, as illustrated by step S88b.

This embodiment is optimal, if there is an automatic client
25 capability report implemented from the WAP user agent / an MExE environment (not shown) to the WAP server / MExE server (not shown).

Fig. 9 shows a signaling usable for the registration of
30 supplementary services (SS) in an MSP environment according to a first implementation.

In a step S91, a user selects to modify supplementary service data (SS data), while in a following step S92,
35 he/she enters (modified) SS data. In a subsequent step S93,

a determination takes place at the user agent side as to which profile type is determined by these data. Namely, in the illustrated case it is distinguished between a standard profile (e.g. a GSM SS based one) or an IN based service
5 profile, i.e. a CAMEL based profile.

It is also possible that the services included in the user profiles are CAMEL based while the services independent of the user profile registered are standardized GSM
10 supplementary service based. The degree of services supported as CAMEL based depends on the MSP version supported in the current environment. Anyhow, it is determined, depending on the profile selected and the MSP version supported, whether a given service is GSM SS based
15 or CAMEL based.

Depending on this determination, two different cases have to be distinguished.

20 In a case A (still depicted in Fig. 9A), in which a standard profile has been determined, in a step S94a, a request for SS registration is forwarded from the user agent to the mobile station via an API (Application Programming Interface). Then, in the subsequent steps S95a,
25 S96a, the command to register the SS data is forwarded from the terminal MS via the MSC/VLR to the HLR. Upon registration thereof at the HLR, the HLR returns a response, step S97a, to the MSC/VLR, which response is relayed via the MS (step S98a) to the user agent again
30 (step S99a).

In a case B (cf. Fig. 9B) different steps are carried out in the profile type is a IN based service profile. Then, in a step S94b, SS information is posted from the user agent
35 to the WAP gateway, and from there (step S95b) to the WAP

server, which forwards the information (step S96b) to the CAMEL service environment CSE. The CSE sends a response (step S97b) to the WAP server, which forwards the same to the WAP gateway (step S98b), which sends the response back
5 to the user agent (step S99b).

With such an implementation, the user interface hides from the user the fact whether the current profile is a standard one, in which the services are standard GSM supplementary
10 services, or whether the current profile is a IN based one, in which the services are implemented using CAMEL.

Fig. 10 shows a signaling usable for the registration of supplementary services (SS) in an MSP environment according
15 to a second implementation.

In a step S1001, a user selects to modify supplementary service data (SS data), while in a following step S1002, he/she enters (modified) SS data. In a subsequent step (not
20 shown) similar to step S93, a determination takes place at the user agent side as to which profile type is determined by these data. Namely, in the illustrated case it is distinguished between a standard supplementary service profile (e.g. a GSM SS based one) or a IN based
25 supplementary service profile, i.e. a CAMEL based profile.

Depending on this determination, two different cases have to be distinguished.

30 In a case A, if the service profile is determined to be of a standard type, the MS registers SS data in a step S10003a to the MSC/VLR, which in a step S1004a in turn registers the SS data to the WAP gateway. The WAP gateway in a step S1005a registers the SS data to the HLR. The HLR functions
35 as a detection point DP on SS registration and informs the

CSE accordingly (step S1006a). In response thereto, the CSE forwards in a step S1007a an instruction to the HLR to continue registration of SS data. The HLR then sends a response to the WAP gateway (step S1008a), which forwards
5 the response, in step S1009a to the MSC/VLR, which in turn informs the terminal MS of the response (step S10010a).

If, however, a profile of IN based type is present (case B in Fig. 10B), the terminal MS forwards a SS registration
10 request in step S1003b to the MSC/VLR, which transmits the same in step S1004b to the WAP gateway. The WAP gateway relays the request in step S1005b to the HLR. Similarly as in case A, the HLR acts as a detection point DP on SS registration and informs the CSE accordingly. The CSE in
15 step S1006c then modifies service data in the CSE for the CSE emulated GSM SS data. In step S1007b, the CSE instructs the HLR to bypass or suspend SS registration, but still to respond to the MSC/VLR as normal. A corresponding response is then transmitted from the HLR to the WAP gateway
20 (S1008b), from there to the MSC/VLR (S1009b), and from there to the MS (step S10010b).

Now, with reference to Fig. 11, this figure shows a signaling scenario for the downloading of MSP menus
25 according to a further embodiment.

Steps S111 and S112 are identical to steps S81 and S82 explained in connection with Fig. 8A earlier above, so that a repeated description thereof is omitted here. The
30 determination of MSP version may also be based on other means than CAMEL version indication to the CSE. For example, it may be determined from the network and/or location identity possibly included in the MS.

In a subsequent step S112a, at the mobile station terminal / user agent side it is checked preferably from the subscriber identity module SIM, whether the identity of the latest mobile equipment has changed. Such an identity may
5 be checked, for example, by referring to the serial number stored in the SIM. Stated in other words, at step S112a a check is performed to obtain an information as to whether the terminal has changed since the latest power on with the same subscription.

10

If the identity of the mobile station has changed, the signaling continues with the steps S113 to S1113.

In step S113, the user agent capabilities are forwarded
15 from the MS/user agent via the WAP-server to the CSE (step S114. This is effected since the CSE inquires information on downloaded services. IN an alternative embodiment, the CSE is indicated by the MS / user agent automatically the downloaded services / software (and/or control instruction)
20 components. The CSE in response thereto returns an indication as to the downloaded services (step S115) via the WAP-server to the MS/user agent (step S116). Information on the downloaded services is thereafter transmitted from the MS / user agent (step S117) to the WAP
25 server and from there (step S118) to the CSE.

At the CAMEL Service Environment CSE, then the following steps are carried out, as shown in Fig. 11B.

30 In step S119, it is checked whether MSP is provisioned. At step S1110 it is checked, whether MSP is downloaded, and possibly also, which MSP phase is downloaded. At step S1111 the user agent capabilities are checked and the content version to be downloaded is selected.

35

The subsequent steps S1112a, S1113a (in a case A) as well as steps S1112b, S1113b (in a case B) are identical to those illustrated and explained in detail in connection with Fig. 8B, so that a repeated description thereof is
5 omitted here.

The described embodiment is advantageous if there is an automatic client capability report implemented from the WAP user agent / MexE environment (mentioned above) to the WAP
10 server / MexE server.

Still further, Fig. 12 illustrates a signaling scenario for a subscriber profile selection in case of an incoming call using WTA.

15

In this case, the called party is identified using only one MSISDN, if the profile selection is to be applied. That is, the MSISDN does not specify the profile for a respective terminated call, while normally, there are different
20 MSISDN's for different profiles. The profile selection service is triggered from a GMSC T-BSCM (not shown). The IN service issues a WTA service indication to the mobile station. The user is then prompted to select the profile which should be used for the terminating (incoming) call.
25 The user may also be presented some information related to the calling party, on the amount and price of calls received for each profile and so on. The selection is passed from the WTA server (WAP server) to the IN service, i.e. the IN service entity. The IN service entity then
30 selects the profile in accordance with the multiple subscriber profiles functionality implementation.

This way of profile selection is advantageous in cases where the called party pays for incoming calls.

35

The above briefly described signaling is now set out in greater detail with reference to Fig. 12, which shows a signaling scenario in connection with a mobile originated call in case a service user interface has not been
5 downloaded to the terminal.

Now, as regards Fig. 12, i.e. Fig. 12A & Fig. 12B, a signaling scenario in connection with a mobile originated call is shown for the case that a service user interface
10 has not been downloaded to the terminal.

In Fig. 12A, in an initial step S21, an initial access message IAM is transmitted from the PSTN (not shown) (i.e. a terminal in the PSTN) to the MSC as a SSP. Alternatively,
15 also a corresponding triggering signal could be received from a visited MSC, i.e. a VMSC or a GMSC. The MSC transfers this, in a step S22, in an InitialDP message and/or operation (InitialDp representing a request for instructing to complete a call) to the service control
20 point SCP such as a CAMEL service environment CSE. The CSE checks in step S22A whether MSP is supported. Also, the CSE, in response thereto forwards in a step S23 a Connect to Resource CTR and play announcement PA message/command to the MSC, since the user must be alerted (with in-band
25 announcement for corresponding notification) for subsequent interaction, and also call set-up timer means (not shown) in a terminal device MS have to be prevented from expiring.

Thereafter, user interaction starts. Namely, in a step S24,
30 information to be displayed (e.g. the profiles available) as well as a service identity is forwarded from the SCE to the associated WAP server. In step S24a, based on the service identity, a WML content skeleton is fetched, which WML content skeleton, in a following step S24b, is filled

with information to be displayed. It is to be noted that the WAP server stores such WML skeletons per each service.

At this stage of the procedure, two cases have to be
5 distinguished.

A first case is a case in which a WTA service indication is used. This means that a content created URL is a WAP server URL including a terminal (e.g. telephone) number MSISDN.

10 Then, in step S25 (Fig. 12B) a WTA service indication in form of a URL-MSISDN is forwarded from the WAP server to the user agent. In response thereto, in step S26, the user agent replies to the WAP server by transmitting a "GET URL-MSISDN request", so that upon receipt thereof at the WAP
15 server, the WAP server transmits, step S27, the URL-MSISDN content to the user agent. Subsequently, in a step S27a, the user is prompted with possible profile identities to be selected. The profile identities may be translated from e.g. numbers to names by MSP content. The user may then
20 select one of the prompted MSP profiles and/or one of the MSP profile identities for the terminating call. This can be effected automatic and done by the MSP content without user assistance, e.g. based on a previous user input. The user may input such selection instructions/commands via the
25 MMI which are collected or accumulated (not shown), and such a user input is, in a step S28, posted from the user agent to the WAP server. Then, the flow ends as regards this branch of the first case.

30 As a second case, a WAP push operation is used, i.e. a WML content is (already) created. In this case, after step S24 (i.e. S24b), the procedure continues with a step S29, in which the WML content is transferred from the WAP server to the user agent. Subsequently, in a step S29a, the user is
35 prompted with possible profile identities to be selected.

The profile identities may be translated from e.g. numbers to names by MSP content. The user may then select one of the prompted MSP profiles and/or one of the MSP profile identities for the terminating call. This can be effected
5 automatic and done by the MSP content without user assistance, e.g. based on a previous user input. As a result, in a step S210 the thus entered and accumulated user input (collected as described before in connection with the first case) is posted from the user agent to the
10 WAP server and the branch of the second case is terminated.

Irrespective of whether the first or second case is present, after the respective steps are completed, the flow continues with a step S211. In step S211, the user input
15 representing the selected profile is transmitted from the WAP server to the service control point SCP (e.g. a CSE). The CSE in turn starts terminating call processing procedures dependent on the selected profile.

20 As described herein before, the present invention proposes a method for providing a user interface between a terminal device and a communication network for configuring intelligent network services, said network comprising a service control entity (SCP, CSE) and a server entity
25 communicating with each other via an interface, said service control entity being connected to at least one service switching device establishing communication via at least one access network with said terminal device, and said terminal device being provided with a browsing means
30 adapted to communicate with a user of said terminal device via a man machine interface means, and adapted to communicate with said server entity, the method comprising the steps of: creating a content which constitutes a user interface for the control of a multiple subscriber profiles
35 (MSP) feature; user interacting with the content; and

modifying the state of the subscriber profiles in
accordance with said user interaction.

5 It should be understood that the above description and
accompanying figures are merely intended to illustrate the
present invention by way of example only. The preferred
embodiments of the present invention may thus vary within
the scope of the attached claims.

CLAIMS

1. A method for providing a user interface between a terminal device (MS) and a communication network (IN-NW) for configuring intelligent network services, said network (IN-NW) comprising

a service control entity (SCP, CSE) and a server entity (WAP- or WTA-SERVER) communicating with each other via an interface (WAP-I/F),

said service control entity being connected to at least one service switching device (SSP, MSC, HLR, VLR) establishing communication via at least one access network (RAN, BSS) with said terminal device (MS), and said terminal device (MS) being provided with a browsing means (WAP-UA) adapted to communicate with a user of said terminal device via a man machine interface means (MMI), and adapted to communicate with said server entity, the method comprising the steps of:

creating a content which constitutes a user interface for the control of a multiple subscriber profiles (MSP) feature;

user interacting with the content; and

modifying the state of the subscriber profiles in accordance with said user interaction.

2. A method according to claim 1, wherein said states of the subscriber profiles comprises the identity of the profile designated as the registered profile, and/or service states, and/or profiles selected for incoming or outgoing calls, and/or the execution states of each service.

3. A method according to claim 1, wherein

the modifying the subscriber profiles state includes the selection of the profile to be used for an outgoing call.

- 5 4. A method according to claim 1, wherein
the modifying the subscriber profiles state includes the selection of the profile to be used for an incoming call.
- 10 5. A method according to claim 1, wherein
said services states comprise service activity / inactivity and/or service parameters for each service.
- 15 6. A method according to claim 1, wherein
said content is loaded into said terminal device (MS) in response to a predetermined event.
- 20 7. A method according to claim 6, wherein
said predetermined event is an IMSI attach, and/or a location updating, and/or a switching on of a new terminal for the user, and/or a subscriber profile registration request, and/or a supplementary service activation / deactivation request, and/or a terminal device originated call set-up request, and/or a terminal device terminated
25 call set-up request.
- 30 8. A method according to claim 6, wherein
said loading is effected from a subscriber identity module (SIM) to said terminal device mobile equipment part (ME).
- 35 9. A method according to claim 6, wherein
said loading of said content is effected from a network element (WAP-SERVER) to said terminal device mobile equipment part (ME).

10. A method according to claim 6, wherein
said content is cached in said terminal device for
later events.

5 11. A method according to any of the claims 2-10, wherein
said registered profile within the subscriber profiles
state is maintained in the service control entity.

12. A method according to claim 11, wherein
10 the selection of said registered profile is
communicated to the service control entity by said browsing
means.

13. A method according to claim 12, wherein
15 the selection of said registered profile is
communicated to the service control entity by the content
issuing a USSD or SMS message to said network, the network
communicating the registered profile to the service control
entity.

20 14. A method according to claim 12, wherein
the selection of said registered profile is communicated to
the service control entity by the content issuing a WSP /
HTTP post method (wireless session protocol / hypertext
25 transfer protocol) to said network, the network
communicating the registered profile to the service control
entity.

15. A method according to claims 2-10, wherein
30 said services states within the subscriber profiles
state are maintained in the service control entity.

16. A method according to claims 2-10, wherein

said services states within the subscriber profiles state are maintained partly in the service control entity and partly in the GSM registers (HLR, VLR).

5 17. A method according to claims 15 or 16, wherein a change in said services states is communicated to the service control entity by said browsing means.

10 18. A method according to claim 17, wherein a change in said services state is communicated to the service control entity by the content issuing a USSD or SMS message to said network, the network communicating the registered profile to the service control entity.

15 19. A method according to claim 17, wherein a change in said services state is communicated to the service control entity by the content issuing a a WSP / HTTP post method (wireless session protocol / hypertext transfer protocol) to said network, the network communicating the registered
20 profile to the service control entity.

20. A method according to any of the previous claims, wherein the selection of the subscriber profile to be used for a terminated call is performed by issuing a content
25 push to said browser means; user interacting with the content; selected subscriber profile indicated to said server entity.

21. A method according to claim 20, wherein
30 the selection of the profile to be used for a terminated call is prompted from the user when the calling party dials a number not explicitly indicating the subscriber profile for the incoming call.

35 22. A method according to claim 1, wherein

the modifying of the state of the subscriber profiles includes the control of the execution of each service.

23. A method according to claim 6, wherein

5 first the capabilities of the said terminal device (MS) and/or user agent capabilities are indicated to said server entity; the said content is selected on the said server entity based on the said capabilities; the said selected content is downloaded to the said terminal device (MS).

10

24. A method according to claim 23, wherein

the capabilities of the said terminal device (MS) and/or user agent capabilities are indicated to said server entity if the mobile equipment part (ME) of the said terminal
15 device has changed since the latest power off of the said terminal device (MS).

25. A method according to claim 23, wherein

first said content is downloaded to said terminal device
20 (MS), if it is discovered that such content is not already stored in said terminal device (MS).

26. A method according to claim 25, wherein

information on the downloaded services is inquired from
25 said terminal device (MS) and the downloading of said content is performed only if it is not among said downloaded services.

27. A method according to any of the previous claims,

30 wherein said content discovers the capabilities of said network when the user attaches to the network or enters the area of a new service switching device (MSC, SSP).

28. A method according to claim 27, wherein

said content modifies the said user interface for the control of a multiple subscriber profiles feature in accordance with said capabilities of said network.

5 29. A method according to claim 27, wherein
said capabilities of the said network is the Camel feature
version supported in said current service switching device
(MSC, SSP).

10 30. A method according to claim 8, wherein
the capabilities of the said terminal device (MS) and/or
browsing means are checked and compared to the capability
requirements of said content before said loading; and if
the capability requirements are not satisfying, downloading
15 said content from said network.

31. A system for providing a user interface between a
terminal device (MS) and a communication network (IN-NW)
for configuring intelligent network services, said system
20 being adapted to operate according to the method according
to claims 1 to 19.

Abstract

The present invention proposes a method for providing a user interface between a terminal device (MS) and a communication network (IN-NW) for configuring intelligent network services, said network (IN-NW) comprising a service control entity (SCP, CSE) and a server entity (WAP- or WTA-SERVER) communicating with each other via an interface (WAP-I/F), said service control entity being connected to at least one service switching device (SSP, MSC, HLR, VLR) establishing communication via at least one access network (RAN, BSS) with said terminal device (MS), and said terminal device (MS) being provided with a browsing means (WAP-UA) adapted to communicate with a user of said terminal device via a man machine interface means (MMI), and adapted to communicate with said server entity, the method comprising the steps of: creating a content which constitutes a user interface for the control of a multiple subscriber profiles (MSP) feature; user interacting with the content; and modifying the state of the subscriber profiles in accordance with said user interaction.

- FIG. 1 -

- 40 -

1/17
FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6



7/17
FIG. 7





FIG. 8A



8/17

FIG. 8B




FIG. 9A

USER AGENT	MS	MSC/VLR	WAP-GW	WAP- SERVER	SSP (HLR)	SCP (CSE)
---------------	----	---------	--------	----------------	--------------	--------------

S91: USER SELECTS TO MODIFY
SUPPLEMENTARY SERVICE (SS) DATA

S92: USER ENTERS
SUPPLEMENTARY SERVICE DATA

S93: DETERMINE PROFILE TYPE:
PRIMARY (e.g. GSM SS BASED) OR
SECONDARY (e.g. CAMEL BASED)

CASE A): IF PRIMARY

S94a: REQUEST SS REGISTRATION VIA API



S95a: REGISTER SS



S96a: REGISTER SS



S97a: RESPONSE




S98a: RESPONSE



S99a: RESPONSE



FIG. 9B



12/17

FIG. 10A






FIG. 10B




14/17

FIG. 11A



15/17

FIG. 11B



CASE A): STEPS S1112a, S1113a, AND CASE B): STEPS S1112b,
S1113b: AS IN FIG. 8B

FIG. 12A




FIG. 12B

